



Datos dimensionales (Pulgadas)				
Dimensional data (Inches)				
MEDIDA SIZE No.	A ±0.002	D MIN	E ±0.015	L ±0.015
16	1.000	1.687	1.562	1.750
18	1.125	1.812	1.687	1.750
20	1.250	1.937	1.812	1.750
22	1.375	2.062	1.937	1.750
24	1.500	2.187	2.062	1.750
26	1.625	2.375	2.250	1.750
28	1.750	2.500	2.375	1.750
30	1.875	2.625	2.500	1.750
32	2.000	2.750	2.625	1.750
34	2.125	2.875	2.750	1.750
36	2.250	3.000	2.875	1.750
38	2.375	3.125	3.000	1.750
40	2.500	3.250	3.125	1.750
42	2.625	3.375	3.250	1.750
44	2.750	3.500	3.375	1.750
46	2.875	3.625	3.500	1.750
48	3.000	3.937	3.812	1.750
50	3.125	4.062	3.937	1.750
52	3.250	4.187	4.062	1.750
54	3.375	4.312	4.187	1.750
56	3.500	4.437	4.312	1.750
58	3.625	4.562	4.437	1.750
60	3.750	4.687	4.562	1.750
62	3.875	4.812	4.687	1.750
64	4.000	4.937	4.812	1.750

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 RPM
 Presion: 450 PSI (32.0Kg/cm²)
 *Temperatura: -59°C ~ 316°C
 *Depende del material del elastómero

OPERATION CONDITIONS

Speed: Up to 3,600 RPM
 Pressure: 450 PSI (32.0Kg/cm²)
 *Temperature: -59°C ~ 316°C
 *Depends on elastomer material

- **Partes Metalicas:** Acero inoxidable 316
Metal Parts: 316 Stainless Steel
- **Resorte:** Hastelloy "C"
Spring: Hastelloy "C"
- **Cara:** Carbón Grafito, Carburo de Silicio
Rotary Face: Graphite, Silicon Carbide
- **Empaque:** NBR (Nitrilo®), FKM (Vitón®), CR (Neopreno®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P) y Silicón (VMQ).
- **Bellow:** NBR (Nitrile), FKM (Viton®), CR (Neopren®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Silicón (VMQ).
- **Asiento:** Cerámica, Carburo de Silicio, Carburo de Tungsteno, Teflón libre de Asbesto, Acero Inoxidable, Ni-Resist.
- **Seat:** Ceramic, Silicon Carbide, Tungsten Carbide, Teflón Asbesto Free, Stainless Steel, Ni- Resist.

